Imãge-X

Product Release













Tweeter with Bass and Treble Adjustments

Custom Conveniences For The Custom Installing Professional

- Very High Sensitivity And Power Handling another way that Earthquake delivers value and performance in one low cost package
- Paintable Grilles for invisible sound
- Turn -N- Lock Installation for safe, efficient and professional installs
- PistonMax Woofer Design for more accurate mid-bass with out distortion
- Poly Injection Composite Drivers for smooth widerange response with low distortion
- Five Models to choose from: Image-5X, Image-6X, Image-8X, Image-C25X and Image-846X
- Long Life, Moisture Resistant Materials including butyl rubber surrounds and poly injection cones for safe use in kitchens, bathrooms and atriums
- Image Style easily integrates with Image in-wall speakers and even Earthquake IQ speakers

SPECIFICATIONS	Imãge 5X	Imãge 6X	Imãge 8X	Imãge C25X
----------------	----------	----------	----------	------------

MSRP	\$ 235.00/pr	\$ 325.00/pr	\$ 389.00/pr	\$ 299.00/pc
Mounting Depth	2 5/8" • 67.3mm	3 1/4" • 83.4mm	3 7/8" • 98mm	3" • 76.2mm
Cut Out Hole	9 9/16" x 6 1/8" 243mm x 155mm	10 5/8" x 7 1/4" 271mm x 185mm	12 7/8" x 8 5/8" 324mm x 220.5mm	16 3/8" x 7 3/8" 339mm x 187.32mm
Grille Frame	11" x 7 9/16" 279mm x 191mm	12 1/8" x 8 5/8" 306.5mm x 220mm	14 1/8" x 10 1/16" 355mm x 255mm	17 5/8" x 8 5/8" 447.67mm x 219mm
Weight	8lbs.	10lbs.	12.40lbs.	7.75lbs.
Finish	White / Paintable	White / Paintable	White / Paintable	White / Paintable
Drive Components	Two-way system using: One 1" silk dome compression tweeter and one 5 1/4" expanded surround poly-mica cone woofer	Two-way system using: One 1" silk dome compression tweeter and one 6 1/2" expanded surround poly-mica cone woofer	Two-way system using: One 1" silk dome compression tweeter and one 8" expanded surround poly-mica cone woofer	Three-way system using: One 1" silk dome compression tweeter and two 5 1/4" expanded surround poly-mica cone woofers
Enclosure	Infinite baffle, flush with wall	Infinite baffle, flush with wall	Infinite baffle, flush with wall	Infinite baffle, flush with wall
Power Handling	20 - 100 Watts	30 - 120 Watts	50 - 200 Watts	40 - 200 Watts
Nominal Impedance	8-Ohm	8-Ohm	8-Ohm	8-Ohm
Sensitivity	92dB @ 1W/1M	91.5dB @ 1W/1M	90dB @ 1W/1M	93dB @ 1W/1M
Frequency Response	65Hz - 21kHz	52Hz - 21kHz	52Hz - 21kHz	50Hz - 21kHz