

# MiniMe P10V2 & P12V2

## Product Release



**INCLUDES:**  
Remote &  
Remote Eye



## Elegance & Style

The MiniMe P10V2/P12V2 amplifier utilizes the advanced class “D” circuitry with over 90% efficiency, allowing it to continuously perform without getting hot.

Earthquake’s own patented SLAPS passive radiator technology dramatically increases the subwoofer’s efficiency and capability for ultra low frequency reproduction. The unique design of the SLAPS employs dual (identical) suspensions, allowing the passive driver to move the same amount of air in either direction. Coupled with the active driver, the SLAPS enables the sub to deliver louder bass without using more power from the amplifier.

The deep luxurious black piano lacquer begins with a thorough sanding and priming, followed by multiple applications of black lacquer with additional fine sanding between each layer, and finished with a smooth, high gloss clear coat.

**Designed For Use In:**  
**Home Theaters & 2-Channel Music Systems**  
**Town Homes/Condos/Apartments**  
**Rooms Up To 22’ x 32’ x 8’**

## Features:

- SLAPS patented passive radiator system
- Passive tuned design for unmeasurable accuracy
- 600-Watt class “D” powered amplifier with automatic signal-sensing turn-on and stand-by mode for longer life, more efficiency and less power consumption (greener)
- Sub operation switch for different ranges
- High gloss multi layer piano black lacquer finish for a mirror shine
- Long throw, premium quality drivers
- Operation status LEDs
- RCA & high level inputs
- Selective variable crossover



**MSRP**  
**MiniMe P10V2** | **\$1,099.00/pc**  
**MiniMe P12V2** | **\$1,399.00/pc**

	MiniMe P10-V2	MiniMe P12-V2
(H) Height w/ feet	12 1/2" (318mm)	15 1/4" (388mm)
(W) Width w/ Amplifier	12 1/4" (312mm)	15 1/16" (382mm)
(D) Depth w/ grille	14" (355mm)	17 1/4" (437mm)