

IMÃGE SERIES

In-Ceiling Speakers



| | (M) (M) (M) (M) (M) (M) | | |
|----------|----------------------------------------|----------------|------------------|
| \ | | CIVI-000 | CIVI-000 |
| | (D) Diameter | 9-7/8" (251mm) | 11-7/16" (290mm) |
| The same | (C) Cut Out Hole | 8-1/4" (208mm) | 9-3/4" (246mm) |
| | (M) Mounting | 3-3/4" (94mm) | 4-3/8" (105mm) |

Rough-N-Kits are available for the CM600 & CM800 RK-IQ6 RK-SS8

OBJECTIVE

The Earthquake Image in-ceiling surround speakers feature a unique adjustable tweeter design that allows custom installers to create enveloping sound fields and localized effects, without disrupting a home's decor.

Designed for surround use in home theater and music applications, the Image in-ceiling series employs a poly injection woofer cone and a single 3/4" neodymium tweeter with silk dome and enhanced high frequency.

The Image in-ceiling speakers out perform conventional designs by maximizing diffusion, clarity and efficiency while minimizing room interaction that blur sonic truth.

INTENDED USE

- √ Contractors, Custom Installers and Retailers
- ✓ New Construction and Retrofit Jobs
- √ Home Theater/5.1 & 2-Channel/Music Systems
- √ Can Be Used in Both Boats and RV's

SPECIAL FEATURES & HIGHLIGHTS

- High efficiency output
- Spring loaded speaker terminals
- Anit-rust grilles
- Available in 6" and 8" models
- High value low cost solution for any job
- Silk, 20mm, swiveling neodymium tweeters
- Low mass poly injection cone bodies for fast and accurate response time
- Wide rubber surround to compliment extra piston area for more musical output
- Paintable grilles and frames to match any decor
- · High quality capacitors and inductors
- Easy to use Turn-N-Lock installation

SPECIFICATIONS CM-600 CM-800 **RMS Power** 100 Watts 125 Watts Handling Frequency 60Hz - 21kHz 45Hz - 21kHz Response 8" Woofer 6-1/2" **MSRP** \$225.00/pr \$265.00/pr