


# FF-10

## Front Firing Powered Subwoofers

Model:  
**FF-10**



**FF-10**

(H) Height w/ feet	13-9/16" (345mm) - including 1/2" (13mm) legs
(W) Width	11-1/2" (292mm)
(D) Depth w/ grille & amp	15-9/16" (395mm)

Front mounted volume control for easy adjustments



### OBJECTIVE

Earthquake's FF-10 subwoofer system was designed to offer consumers budget and volume optimized subwoofer system solutions.

With a small footprint, wide variety of applications and incredible output, this subwoofer comes loaded with features such as: 400-Watt Class "A/B" amplifier, Auto Signal Sensing, Low & High Level inputs and outputs, 0 - 180° phase shift as well as 0 - 40Hz crossover. The output Level of the FF10 exceeds 130dB peak SPL (including room gain) from 25Hz to 125Hz.

Now available in a 10 inch version, the FF-10 subwoofer offers the most value for the price.

### INTENDED USE

- ✓ Contractors, Custom Installers & Retailers
- ✓ Front Firing Applications
- ✓ Budget Home Theaters
- ✓ Town Homes/Condos/Apartments/Restaurants

### SPECIAL FEATURES & HIGHLIGHTS

- Front firing design with small footprint
- Single Slot Port for optimized bass output
- Front mounted volume control
- 400-Watt class "A/B" high efficiency power amplifier
- 12dB/Octavevariable filter from 40 - 180Hz
- Automatic signal detection circuitry - automatically turns on the subwoofer ON/OFF
- Status LED indicators
- Low Level (RCA) & High Level audio inputs
- Line through RCA & High level audio outputs
- 10" high power subwoofers
- 0 - 180° phase shift
- 40 - 180Hz crossover

### SPECIFICATIONS

	<b>FF-10</b>
Amplifier Power	400 Watts
Frequency Response	25 - 125Hz
Weight	26.5 lbs
Finish	Black Ash
MSRP	\$449.00/pc