

EDGELESS Stereo Ceiling Speakers

Product Release



ECS6D



ECS8D



Available with optional square grille (sold separately):
 SG-CS6 for the ECS6D
 SG-CS8 for the ECS8D

Now Available in Stereo/Dual VC Models

Earthquake Sound's **EDGELESS** In-Ceiling Speakers are now also available in dual voice coil/stereo models with Dipole/Bipole and DVC/Surround selectable modes for use in limited/smaller space such as kitchens, hallways, bathrooms, etc.

The standard +/- 3dB adjustment switches combined with the Dipole/Bipole and DVC/Surround selectable modes further optimize the speakers' response to match the acoustics of the room and fulfill the end user's own personal preference.

Their advanced low mass stiff Kevlar cones and wide surrounds allow these Edgeless speakers to deliver deep, natural bass. Beside high efficiency, sonic accuracy is guaranteed by utilizing 1" (25mm) silk dome tweeters.

Designed with aesthetics (WAF-wife approval factor) and sound quality in mind, these speakers seamlessly blend into their surrounding as they provide a lifetime of durability and high-end performance.

Dipole/Bipole Switch



DVC/Surround Switch



± 3dB bass and treble controls



MODEL	MSRP	QTY
ECS6D	\$269.00	Piece
ECS8D	\$299.00	Piece

Features

- Dual voice coil woofer with Kevlar cone bodies
- 1" (25mm) silk dome NEO swiveling tweeters
- Dipole / Bipole and DVC / Surround selectable modes
- Frameless design for reduced visibility/seamless blend
- ± 3dB bass and treble controls
- Turn-N-Lock™ installation mechanism for safe, time efficient and professional installation
- Gold plated, spring loaded terminals

Specifications

	ECS6D	ECS8D
Frequency Response:	40Hz - 20kHz	30Hz - 20kHz
Sensitivity:	87dB @ 1W/1M	88dB @ 1W/1M
Nominal Impedance:	8-Ohm In Dipole Mode 4-Ohm In Bipole Mode	8-Ohm In Dipole Mode 4-Ohm In Bipole Mode
Power Handling:	350 Watts Max	450 Watts Max
Enclosure Type:	Impact resist ABS Plastic	
Driver Components:	Two-way system using one 6.5" Kevlar cone midbass and two 1" silk dome swiveling NEO tweeters	Two-way system using one 8" Kevlar cone midbass and two 1" silk dome swiveling NEO tweeters
Outer Diameter:	8 9/16" (223mm)	10 1/2" (267mm)
Cut Out Diameter:	7 7/8" (200mm)	9 1/2" (242mm)
Mounting Depth:	4 5/16" (110mm)	4 7/8" (124mm)
Grille:	White / Paintable, Magnetically Attached	